

BEIYANG BTP-2002NP Thermal Receipt Printer



Print specification

- Method: Direct Thermal
- Resolution: 203DPI
- Print Width: 80mm
- Print Speed: Up to 200mm/s
- Memory: RAM: 2M FLASH: 1MB
- Printing mode: Standard mode, page mode, bit-image mode
- Print length: No limit at standard mode, max. 150mm at other modes
- Drivers: Windows drivers (WIN98/NT/2000/XP/Vista)
- Cash drawer control 1 to 2 drawers

Sensors

- Print head overheating protection
- print head position,
- paper near end
- paper out

Interface

Centronics, RS232C, RS485/422, USB ,Ethernet,Wireless

Cash drawer

Connector for one or two cash drawers (use a "Y"cord for two drawers.)

Bar Code Supported

UPC-A, UPC-E, EAN13, EAN8, CODE39, CODE93, Interleaved 2 of 5, CODABAR, CODE128, PDF417

Resident fonts

- Standard: 12*24 Compressed: 9*17

- CODE PAGE: 437,850,852,860,863,865,858,866,PC1252,katakana
- User-defined fonts:support,can download to RAM or FLASH

Character Modification

- Rotate (0,90,180,270 angle)
- enlarges (1~6X)
- emphasize, underline, white/black reverse

Graphic Printing

- Non bit-image mode Print with unit of 24 dots per line
- Bit-image mode The print unit is one dot-line to realize fast speed curve printing
- Bit Image Download:support,can download to RAM or FLASH
- Configuration mode:Save 64 words printer configuration information when power off

Paper specification

- Type: Direct thermal paper
- Width: 57.5,69.5,76,80,82.5mm
- Weight: 60 g/m²
- Roll Diameter (max.): 83 mm
- Paper cutting Mode: Automatic cutting or tear off, Full cut, Partial cut

Spec. Of AC adaptor

- Input: 100-240VAC, 50-60HZ
- Output: 24VDC, 2.5A

Reliability

- Printer head lifetime 100 Km or more
- Cutter lifetime 1,500,000 cuts (standard thermal paper, 0.06-0.1 mm)

Physical Spec.

- Dimensions: 144 (W)x 192 (D) x 142 (H) mm
- Weight:2kg

Environment

- Operating temperature 5~45degrees
- Operating humidity 20-90%RH (no condensation)
- storage temperature:-40~60degrees
- storage humidity: 20-93%RH(40degrees)

Other Cabinet Color

- Ivory, Black